
S3-070270-NF



3 Way High Powe Splitter,700-2700MHz,NF



Specifications

General Specification	
Application	Indoor/Outdoor
Color	Black
Inner Contact Plating	Silver
Interface	N female
Outer Contact Plating	Tri metal
Housing	Passivated Aluminum or powder paint
Mounting	Bracket for wall mounting included in the scope of supply
Dimensions	-
Length*Width*Height	227 mm * 60.8 mm * 25 mm
Weights	
Weight, net	0.42 kg
Electrical Specification	
PIM, Passive IM	-150 dBc, 2x43 dBm
Power Rating, Max	500 W; 3 KW Peak
Input Impedance	50 ohm
Frequency Range	700-2700 MHz
VSWR, Max	1.25
Split	3
Insertion Loss, Max	0.1 dB
Split Loss	4.8 dB
DC capability	DC transmission between all ports

ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

S3-070270-NF



3 Way High Powe Splitter,700-2700MHz,NF

Environmental Specification

Temperature Range	-35 °C to +75 °C
Ingress Protection Test Method	IP65
Regulatory Compliance	
ROHS	Compliant

ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.